# PLEXCHEM TECHNOLOGIES



# PLEXSTAB® - 5261

### **Characteristics**

**PLEXSTAB**<sup>®</sup> **5261** is a stabilizing component based on elastomer modified polyethylene and active stabilizers for use in power insulation application. It is in the form of free flowing powder to allow easier mixing in the compounding of silane crosslinked PE compound. It has increased stabilization with respect to metal deactivation in the presence of free copper ions.

## **Application**

**PLEXSTAB<sup>®</sup> 5261** is designed to fulfill the heat and chemical stabilization requirement of insulation with or without the presence of copper. It can be used in the silane crosslinking systems to meet IEC aging requirements. Dosage rate is generally between 3%. The typical properties of finished insulation compound made using **PLEXSTAB<sup>®</sup> 5261** will be as follows;

Properties	Test Method	Unit	Value
Tensile strength @ break	IEC 811	MPa	>16
Ultimate Elongation	IEC 811	%	>650
Change in Tensile strength @ break after aging**	IEC 811	%	>15
Change in Tensile strength @ break after aging**	IEC 811	%	>15
Hot set requirements	IEC 811	%	>80

\*\* : Aging @ 135  $^{\circ}$ C for 7 days

#### **Technical Data**

Properties		Component	(%)
Physical form :	Powder	Carrier Resin	96.7
Color :	Brownish/		
Moisture :	yellow		< 200 ppm
moisture.			~ 200 ppin

#### Storage and Handling

**PLEXSTAB<sup>®</sup> 5261** is supplied in powder form, packed in 25 kgs bags with a sealed inner liner. Unopened bags can be stored for 3 year. Store bags in shaded area away from sunshine and rain.

This product can be readily conveyed and fed through conventional equipment for the production of Silane Crosslinked polyethylene.

The information contained herein is to the best of our knowledge accurate but since the circumstances and conditions in which it may be used are beyond our control, we do not accept liability for any loss or damage, however arising, which results directly or indirectly from the use of such information. This document shall form no part of any control with a customer. Do you have the safety data sheet for this product? Please contact you service representative for one or E-mail us at:

Do you have the safety data sheet for this product? Please contact you service representative for one or E-mail us at: plexchem@plexchem.com.sg



PLEXLINK is a product of PLEXCHEM TECHNOLOGIES an ISO 9001 accredited company. Certificate number