



PA-1

Processing Aid Masterbatch

Characteristics

PA-1 is an additive concentrate which contains processing aid to eliminate or reduce melt fracture and die build-up during processing of LLDPE and HDPE. It is also effective in increasing throughput and reducing power consumption.

Application

The typical dosage level of **PA-1** is 2.0 to 4.0% depending on the desired effects.

Technical Data

Properties

Physical form :	Solid pallet
Color :	Natural
Odor :	non
Sp. Gravity @ 23 °C :	0.95
MFI @ 190oC	4 g / 10 min

This is a fluorocarbon compound.

Storage and Handling

PA-1 is supplied in pallet form, packed in bags.
Store bags in shaded area, away from sunshine and rain.

This product can be readily conveyed and fed through conventional equipment designed for palletized polyethylene.

The information contained herein is to the best of our knowledge accurate but since the circumstances and conditions in which it may be used are beyond our control, we do not accept liability for any loss or damage, however arising, which results directly or indirectly from the use of such information. This document shall form no part of any control with a customer.

Do you have the safety data sheet for this product? Please contact your service representative for one or E-mail us at: plexchem@plexchem.com.sg



PLEXLINK is a product of PLEXCHEM TECHNOLOGIES an ISO 9001 accredited company.

Certificate number 1468/97